

LEARTHHERM GLASS SEALED UNITS LIMITED

TOUGHENED GLASS PROCESSORS
SPECIALISTS IN WARM EDGE TECHNOLOGY

125a / 125b Barkby Rd., Leicester LE4 9LG • Tel: (01162) 460137 • Fax: (01162) 461478
Email: sales@cleartherm.com • Web site: www.cleartherm.com

WARM EDGE TECHNOLOGY GEORGIAN LEADED STAINED GAS FILLED

CE

Cleartherm Glass Sealed Units Ltd. 125a/b Barkby Road, Leicester,
LE4 9LG

13
BE EN 1279-5

Certificate of Consistency of performance Ref 1121-CPR-CA 5012
c/003

D.O.P ref: CGSU.CE.1279-5 2005 + AZ 2010

Cleartherm Glass Sealed Units Ltd Incorporating Pilkington Pyrodur

Intended use: Fire resistant Insulating Glass Units to be used in Buildings and
Construction works.

Pilkington Pyrodur 30-105 / Galvanised Steel Spacer / 6.8 Pilkington Optilam (worst
case scenario IGU shown - individual calculations available on request)

Characteristics:

Resistance to fire	EW30
Resistance against sudden temperature changes and temperature differentials	≥ 40+40K
Thermal properties	2.7W/m ² K
Direct Airborne Sound Insulation	35 (-1;-3 dB)
Burglar Resistance	NPD/ P (2) A


